

...designed for perfect signals

## DC2150: 850MHz – 2450MHz, Coupling 2 x -20dB

The DC2150 is a directional coupler for L-Band (950 – 2150MHz) and extended L-Band applications (850 – 2450MHz). It is especially designed for use in combination with our dual RF-Power Meter PwrM3G but can of course also be operated independently.

Corresponding 1RU/19" rack mount chassis allow insertion of 1 or up to 8 DC2150 directional couplers.



### TECHNICAL SPECIFICATIONS

<b>Dimensions (Module):</b>	100 x 60 x 15mm high
<b>Weight (Module):</b>	250 g
<b>Dimensions Chassis:</b>	1RU/19" rack mount
<b>Frequency Range:</b>	850MHz – 2450MHz
<b>RF Power:</b>	10W max.
<b>Insertion Loss Main:</b>	950 – 2150MHz -0,5dB ±0,25dB, 850 – 2450MHz -0,75dB ±0,4dB
<b>Coupling:</b>	950 – 2150MHz 2 x -20dB ±0,25dB, 850 – 2450MHz 2 x -20dB ±0,5dB
<b>RF Connector:</b>	SMA(f)
<b>Return Loss:</b>	< -18dB all ports
<b>Operating Temperature:</b>	0°C to 45°C
<b>Storage Temperature:</b>	-10°C to 70°C
<b>Humidity:</b>	90%, non-condensing
<b>RoHS:</b>	Compliant

### ORDER INFORMATION

Type	Type No.	Short Description	Connectors
DC2150	9000908	L-Band / Ext.-L-Band Directional Coupler -20dB	4 x 50Ohm SMA(f)
SP2150-12-50S	9001164	L-Band / Ext. L-Band Passive 1:2 Splitter for output expansion	3 x 50Ohm SMA(f)
DC2150-1-1RU-Chassis	9001079	1RU/19" rack mount mounting panel, 1 slot	n.A.
DC2150-8-1RU-Chassis	9001063	1RU/19" rack mount mounting panel, 8 slots	n.A.